





PRODUCT DETAILS	
Product Code	NM105
Collection	Natureffect Mineral Core SPC
Construction	Calcium-plastic Composite Core with integrated IXPE underlay
Specie	N/A
Product Type	SPC Plank
Surface	Textured Wood Effect
Finish	Ultra Matt UV Coating
Joint Type	UniClic Locking System
Edge Profile	Micro Bevel Edged on 4 sides
Core Layer	Calcium-plastic Composite Core
Dimensions	228 x 5 x 1220m
Pack Size	2.503m²
Pack Contents	9 Boards
Grade	Rustic Pattern

TECHNICAL CRITERIA	
Origin	Turkey
Responsible Certification	N/A
Dimensional Stability	ISO 23999 / Class 34
Formaldehyde Emission	EN 717-1 (Test result E1)
Slip Resistance	EN13893 - DS
Thermal Resistance	EN 12667 (Test result: 0.296 W/mK)
European Reaction to Fire Certification	EN 11925-2 (test result Bfl-s1)

INSTALLATION METHODS	
Fully Bonded	No
Secret Nailed	No
Floated on Underlay	Yes* (Built in underlay)
V4Magnetic®	No
Over Underfloor Heating	Yes*

^{*} Subject to correctly prepared and compatible subfloor, in conjunction with correct installation and usage.

^{**}Find out more at www.v4.co.uk/v4magnetic



INSTALLATION - IMPORTANT GUIDANCE

Installation of your V4 floor is considered acceptance of goods.

All V4 floors must be installed by an experienced and fully competent flooring installer who has the necessary skills to complete each installation in line with the BS8201:2011 standard. The responsibility for inspection of goods lies with the installer, and it is their duty to notify V4 of any potential concerns prior to installation.

DO NOT COVER AN INSTALLED FLOOR WITH A NON-BREATHABLE COVERING FOR LONGER THAN 1 WEEK.

Prolonged covering may create a microclimate which can damage the protective top layer. Underfloor heating will greatly magnify the effect. For full guides visit $\underline{v4.co.uk/support}$ or scan the Product QR code.