



ZB205 Black Walnut



PRODUCT DETAILS

Product Code	ZB205
Collection	Deco Parquet
Construction	Multi Layered
Specie	American Black Walnut
Product Type	Engineered Herringbone
Surface	Smooth Sanded
Finish	UV Oiled
Joint Type	Tongue & Groove
Edge Profile	Bevel Edged on 4 sides
Core Layer	11mm Multi-layer: Poplar & Eucalyptus
Dimensions	90 x 14/3 x 400 mm
Pack Size	1.44m ²
Pack Contents	40 Boards
Grade	Mixed Grade

TECHNICAL CRITERIA

Origin	China
Responsible Certification	UKTR
Janka Hardness Rating	Walnut 1010 lbf (4490N)
Formaldehyde Emission	EN 717-1 (Test result E1)
Slip Resistance	EN 14231 (Test Result 80/46 PTV)
Thermal Conductivity	EN 12524 (Test Result: 0.16 W/mK)
European Reaction to Fire Certification	EN 13501-1 (test result Dfl-s1)

GRADING

A mixture of Rustic & Select/Nature grades within packs. Mixed Grade displays variation in grain and colour with larger sound & filled knots with more sapwood well distributed. Small, filled cracks & dark streaks are also apparent. The filler colour is chosen to complement the wood's natural structure, highlighting knots with a contrasting effect that may vary between batches, adding to its unique rustic charm.

N.B The product grading criteria is inspected at each mill visually and should be taken as an approximation only.
Please ask for further details.

INSTALLATION METHODS

Fully Bonded	Yes*
Secret Nailed	No
Floated on Underlay	No
V4Magnetic®	Yes**
Over Underfloor Heating	Yes*

* Subject to correctly prepared and compatible subfloor, in conjunction with correct installation and usage.

**Find out more at www.v4.co.uk/v4magnetic

INSTALLATION – IMPORTANT GUIDANCE

Installation of your V4 floor is considered acceptance of goods.

All V4 floors must be installed by an experienced and fully competent flooring installer who has the necessary skills to complete each installation in line with the BS8201:2011 standard. The responsibility for inspection of goods lies with the installer, and it is their duty to notify V4 of any potential concerns prior to installation.

DO NOT COVER AN INSTALLED WOOD FLOOR WITH A NON-BREATHABLE COVERING FOR LONGER THAN 1 WEEK.

Prolonged covering may create a microclimate which can damage the protective top layer. Underfloor heating will greatly magnify the effect. For full guides visit v4.co.uk/support or scan the Product QR code.

