




V4 Wood Flooring®

ZB204 Shore Drift Oak

Technical Data Sheet



Product Details:

Product Code	ZB204
Collection	Deco Parquet
Construction	Engineered
Species	Oak
Product Type	Engineered Parquet Block
Surface	Brushed
Finish	Invisible Matt Lacquer
Dimensions	90 x 14/3 x 400 mm
Top Layer	3 mm – Solid European Oak
Core Layer	11 mm – Multi-Layer Eucalyptus & Poplar
Grade	CD Rustic
Pack Size	1.44 m ²
Pack Contents	40 Boards
Joint Type	3 Grooves 1 Tongue
Edge Profile	Bevel Edged on 4 sides

Technical Information:

Origin	Europe
UKTR / UK Timber Regulation	Full documented evidence of legality of timber
FSC® Certification	FSC®100% (TT-COC-004200)
PEFC® Certification	Not available with this product
Janka Hardness	Oak 1360 lbf (6000N)
Slip Resistance	EN 14231 (Test Result 64/32 PTV)
European Reaction to Fire Classification	EN 13501-1 (test result Dfl-s1)
Release of Formaldehyde	EN 717-1 (Test result E1)
Thermal Conductivity	EN 12524 (Test result: 0.16W/mK)
Tog Rating	1.13

Installation Methods:

Fully Bonded	Yes*
Secret Nailed	No
Floated on Underlay	No
Over Underfloor Heating	Yes* (fully bonded installation recommended)
V4 Magnetic	Yes*

All V4 floors must be installed by an experienced and fully competent flooring installer who have the necessary skills to complete each installation in line with the BS8201:2011 standard. The responsibility of inspection of goods lies with the installer, and it is their duty to notify V4 of any potential concerns prior to installation. Installation of your V4 floor is considered acceptance of goods.
*Subject to correctly prepared and compatible subfloor and in conjunction with correct installation.

Grading: Rustic

ZB204 is a rustic grade floor, meaning it will contain varying amounts of live and dead filled knots. In addition, the floor will contain Heartwood and Sapwood, offering a wider range of colour variation, and Expert Checks can be expected (cracks along the growth ring). The colour of the filler used on this floor is intended to complement the natural structure of the wood, and such may contrast the surrounding timber, as can be seen in knots. This may vary from batch to batch.

Maintenance: Lacquered Floor Care



Sweep with a soft bristle brush, or the parquet attachment on your vacuum cleaner. Always ensure you are using PH Neutral cleaners and avoid soaking the floor with water. Avoid scratches by minimising grit and dust, install doorway entrance mats and felt pads to protect furniture. Scan the QR code to visit our Lacquered Floor Care page on our website, for more details.

Further Information:



Scan this QR code to visit the ZB204, Shore Drift Oak product page on our website, where you can find more information on the installation and maintenance, make an enquiry and order your free sample.

Post-Installation:

DO NOT COVER THIS PRODUCT WITH A NON-BREATHABLE COVERING FOR LONGER THAN 1 WEEK. Prolonged covering may create a microclimate which can damage the protective top layer. Underfloor heating will greatly magnify the affect.



The mark of responsible forestry

V4 Wood Flooring®

Call +44(0)1276 488099
Email team@v4woodflooring.co.uk
Visit www.v4woodflooring.co.uk

© This technical data sheet was written by V4 Wood Flooring Ltd. Greenbays Park Carthouse Lane, Horsell, Surrey GU21 4YP. At the time of writing and publication of sheet, all the information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. It is the duty of the customer to confirm the specification of their chosen floor upon purchasing. Wood flooring is a natural product with variation in colour, the colour representation in this picture is for illustrative purposes only and no rights can be derived from them. Please use product images as a guide in conjunction with the website and product samples.