



Product Specification	
Product Code	DC205
Collection	Deco Plank
Construction	Engineered
Species	American Black Walnut
Product Type	Engineered Plank
Surface	Smooth Sanded
Finish	UV Cured Oiled
Dimensions	190 x 14/3 x 1900 mm
Top Layer	3 mm - Solid American Black Walnut
Core Layer	11 mm – Multi-Layer: Poplar & Eucalyptus
Grade	ABC Mixed Grade
Pack Size	2.888 m ²
Pack Contents	6 Boards – May Include 2 split lengths
Joint Type	Tongue & Groove
Edge Profile	Bevel Edged on 4 sides

Grading: Mixed Grade

A mixture of Rustic & Select/Nature grades within packs. Mixed Grade displays variation in grain and colour with larger sound & filled knots with more sapwood well distributed. Small, filled cracks & dark streaks are also apparent. V4 Wood Flooring is chosen for its natural beauty, therefore grading criteria is always an approximation as every piece of timber is different. If further selection is needed, please allow for extra material upon installation.

Technical Information

Origin	China
UKTR/ UK Timber Regulation	Compliant
FSC® Certification	Not available with this product
PEFC® Certification	Not available with this product
Janka Hardness	North American Walnut 1,010 lbf (4,500 N)
Slip Resistance	EN 14231 (Test Result 56/42 PTV)
European Reaction to Fire Classification	EN 13501-1 (test result Dfl-s1)
Release of Formaldehyde	EN 717-1 (Test result E1)
Thermal Conductivity	EN 12524 (Test result: 0.16W/mK)

Installation Methods

Fully Bonded	Yes*
Secret Nailed	No
Floated on Underlay	Yes*
V4Magnetic®	Yes**
Over Underfloor Heating	Yes*

* Subject to correctly prepared and compatible subfloor in conjunction with correct installation and usage.

** Find out more at www.v4.co.uk/v4magnetic

Installation - Important Guidance:

All V4 floors must be installed by an experienced and fully competent flooring installer who has the necessary skills to complete each installation in line with the BS8201:2011 standard. The responsibility for inspection of goods lies with the installer, and it is their duty to notify V4 of any potential concerns prior to installation. **Installation of your V4 floor is considered acceptance of goods.**

For full guides visit v4.co.uk/support or scan the Product QR code below.

Post Installation - Important Note:

DO NOT COVER AN INSTALLED WOOD FLOOR WITH A NON-BREATHABLE COVERING FOR LONGER THAN 1 WEEK. Prolonged covering may create a microclimate which can damage the protective top layer. Underfloor heating will greatly magnify the effect.

Scan QR code for more product info:

- Installation Guides
- Underfloor Heating Advice
- Maintenance Schedule
- Floorcare Advice
- Product Images
- Room Visualiser
- Order FREE samples

Commercial Enquiry

Tel +44(0)1276 859111
Email design@v4.co.uk

Residential Enquiry

Tel +44(0)1276 488099
Email enquiries@v4.co.uk