




# NAL52 Hammer Beam Oak



## Technical Information

Origin	Europe
UKTR/ UK Timber Regulation	Compliant
FSC® Certification	Not available with this product
PEFC® Certification	Not available with this product
Wear	EN 13329 AC4 / Class 32
Slip Resistance	DS
European Reaction to Fire Classification	C <sub>ii</sub> -S1
Release of Formaldehyde	EN 717-1 (Test result E1)
Thermal Conductivity	EN 12524 (Test result: 0.075 W/(mK))
Tog Rating	0.7

## Installation Methods

Fully Bonded	No
Secret Nailed	No
Floated on Underlay	Yes*
V4Magnetic®	Yes**
Over Underfloor Heating	No

\* Subject to correctly prepared and compatible subfloor in conjunction with correct installation and usage.

\*\* Find out more at [www.v4.co.uk/v4magnetic](http://www.v4.co.uk/v4magnetic)

## Product Specification

Product Code	NAL52
Collection	Natureffect Aqualock
Construction	Laminate HDF
Species	Pine HDF
Product Type	Laminate Flooring
Surface	Embossed
Finish	AC4 Rated PU Coating
Dimensions	192 x 8 x 1285 mm
Top Layer	PU Coated Paper Foil
Core Layer	Pine HDF
Grade	Rustic Pattern
Pack Size	1.973 m <sup>2</sup>
Pack Contents	8 Boards
Joint Type	Locking System
Edge Profile	Bevel Edged on 4 sides

## Installation - Important Guidance:

All V4 floors must be installed by an experienced and fully competent flooring installer who have the necessary skills to complete each installation in line with the BS8201:2011 standard. The responsibility for inspection the of goods lies with the installer, and it is their duty to notify V4 of any potential concerns prior to installation. Installation of your V4 floor is considered acceptance of goods.

For full guides visit [v4.co.uk/support](http://v4.co.uk/support) or scan the Product QR code below.

## Post Installation - Important Note:

DO NOT COVER AN INSTALLED WOOD FLOOR WITH A NON-BREATHABLE COVERING FOR LONGER THAN 1 WEEK. Prolonged covering may create a microclimate which can damage the protective top layer. Underfloor heating will greatly magnify the effect.

## Scan QR code for more product info:



- Installation Guides
- Underfloor Heating Advice
- Maintenance Schedule
- Floorcare Advice
- Product Images
- Room Visualiser
- Order FREE samples

Explore our full range of flooring solutions at [v4.co.uk](http://v4.co.uk)

### Commercial Enquiry

Tel +44(0)1276 859111

Email [design@v4.co.uk](mailto:design@v4.co.uk)

### Residential Enquiry

Tel +44(0)1276 488099

Email [enquiries@v4.co.uk](mailto:enquiries@v4.co.uk)

2024© This technical data sheet was written by V4 Wood Flooring Ltd. Greenbays Park Carthouse Lane, Horsell, Surrey GU21 4YP. At the time of writing and publication of sheet, all the information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this sheet are intended only as illustrations. No rights can be derived from them.