

NAL54 Granary Oak



Product Specification	
NAL54	
Natureffect Aqualock	
Laminate HDF	
Pine HDF	
Laminate Flooring	
Embossed	
AC4 Rated PU Coating	
192 x 8 x 1285 mm	
PU Coated Paper Foil	
Pine HDF	
Rustic Pattern	
1.973 m²	
8 Boards	
Locking System	
Bevel Edged on 4 sides	

Technical Information	
Origin	Europe
UKTR/ UK Timber Regulation	Compliant
FSC® Certification	Not available with this product
PEFC® Certification	Not available with this product
Wear	EN 13329 AC4 / Class 32
Slip Resistance	DS
European Reaction to Fire Classification	C _{ff} -S1
Release of Formaldehyde	EN 717-1 (Test result E1)
Thermal Conductivity	EN 12524 (Test result: 0.075 W/(mK)
Tog Rating	0.7
Installation Methods	
Fully Bonded	No
Secret Nailed	No
Floated on Underlay	Yes*
V4Magnetic®	Yes**
Over Underfloor Heating	No

- * Subject to correctly prepared and compatible subfloor in conjunction with correct installation and usage.
- ** Find out more at www.v4.co.uk/v4magnetic

Installation - Important Guidance:

All V4 floors must be installed by an experienced and fully competent flooring installer who have the necessary skills to complete each installation in line with the BS8201:2011 standard. The responsibility for inspection the of goods lies with the installer, and it is their duty to notify V4 of any potential concerns prior to installation. Installation of your V4 floor is considered acceptance of goods.

For full guides visit v4.co.uk/support or scan the Product QR code below.

Post Installation - Important Note:

DO NOT COVER AN INSTALLED WOOD FLOOR WITH A NON-BREATHABLE COVERING FOR LONGER THAN 1 WEEK. Prolonged covering may create a microclimate which can damage the protective top layer. Underfloor heating will greatly magnify the effect.

Scan QR code for more product info:



- Installation Guides
- Underfloor Heating Advice
- Maintenance Schedule
- Floorcare Advice
- Product Images
- Room Visualiser
- Order FREE samples

Explore our full range of flooring solutions at v4.co.uk